

ADAM-5560CDS

7-slot PC-based Intel® Atom™ CPU soft logic Controller with integrated target visualization

NEW



Features

- Cost effective DIN Rail IPC with VGA port for integrated target visualization
- Optional CoDeSys web Visu for Remote monitoring using Web browser based HMIs
- Free of charge CoDeSys V3 IEC-61131-3 development tool
- Supports five logic programming languages (LD,IL,FBD,SFC,CFC)
- Supports Modbus/RTU (Master/Slave) and Modbus/TCP (Server/Client)
- Supports SD Storage I/O Module
- Fully integration of all Advantech Modbus TCP/RTU remote I/O modules of the ADAM 4000/6000 series
- Seven I/O expansion slots supporting a wide range of cost effective local I/O Modules
- Two alternative slots for serial communication expansion (RS-232/422, CAN)

Introduction

The ADAM-5560CDS is a cost effective DIN RAIL IPC for control and data acquisition tasks which require Industrial PC computing performance with a PLC's robustness. The ADAM-5560CDS, is equipped with an Intel Atom CPU, along with control specific features such as watchdog timer, battery backup RAM and deterministic I/O. The ADAM-5560CDS features five standard IEC 61131-3 programming languages in Windows CE, so PLC users can develop control strategies with their own familiar programming languages such as LD,IL,FBD,SFC,CFC. The powerful CoDeSys V3 Development Software and CoDeSys Integrated stable run time allows the ADAM-5560CDS to become the best choice for building cost effective, compact and reliable control solutions on the market today. With integrated target visualization HMI software and built-in VGA port there is no need to develop software for an additional Operator Panel. The additional optional CoDeSYS web Visu allows easy integration for remote monitoring through cost effective browser based HMI terminals or mobile devices. The powerful and flexible ADAM-5560CDS DIN RAIL IPC controller is ideal for a variety of control and data acquisition applications ranging from factory facilities, green house automation, water and waste water to environmental monitoring.

Specifications

Control System

- **CPU** Intel Atom Z510P
- **I/O Capacity** 7 slots
- **LED Indicators** Power, User defined
- **Memory** 1 GB DDR2 SDRAM
- **Storage** 1 x CompactFlash® Card (Internal, 1 GB)
- **Operating System** Windows CE5.0
- **Real-time Clock** Yes
- **Watchdog Timer** OS and Application

Protection

- **Communication** RS-485 Isolation 1.5 kV for COM1, COM3 and COM4
RS-485 Isolation 2.5 kV for COM2
- **Power Reversal** Yes

Power

- **Power Consumption** 17W @ 24 V_{DC} (Not include I/O modules)
- **Power Input** 12 ~ 24 V_{DC}, ± 20%

General

- **Certification** CE, FCC Class A
- **Dimensions** 355 x 110 x 75 mm
- **Enclosure** ABS+PC
- **Mounting** DIN-rail, wall mount (panel mount)
- **Plug-in Screw Terminal** Accepts 0.5 mm² to 2.5 mm², 1 - #12 or 2 - #14 to #22 AWG

I/O Interfaces

- **Serial Ports** 1 x RS-485, Terminal, 50~115.2kbps
3 x RS-232/485, DB9, 50~115.2kbps
- **LAN Ports** 2 x RJ-45, 10/100Mbps
- **USB Ports** 2 x USB 2.0
- **Displays** 1 x VGA, supports 1024 x 768

Environment

- **Humidity** 5% to 95%, non-condensing
- **Operating Temperature** 0 ~ 55°C (32 ~ 131°F)
- **Storage Temperature** -25 ~ 85°C (-13 ~ 185°F)

Ordering Information

- **ADAM-5560CDS** 7-slot PC-based Controller with Intel Atom CPU and CodeSYS V3 Runtime with target visualization

| Part Number | Description | Part Number | Description |
|-------------|---|-------------|--|
| | Analogue I/O Module | | Digital I/O Module |
| ADAM-5013 | 3-ch RTD Input | ADAM-5051 | 16-ch DI |
| ADAM-5017 | 8-ch AI | ADAM-5051D | 16-ch DI w/LED |
| ADAM-5017P | 8-ch AI w/Independent Input Range | ADAM-5051S | 16-ch Isolated DI w/LED |
| ADAM-5018P | 7-ch TC Input w/Independent Input Range | ADAM-5052 | 8-ch Isolated Differential DI |
| ADAM-5017UH | 8-ch Ultra High Speed AI | ADAM-5056 | 16-ch DO |
| ADAM-5024 | 4-ch AO | ADAM-5056D | 16-ch DO w/LED |
| ADAM-5018 | 7-ch TC Input | ADAM-5056S | 16-ch Isolated DO w/LED |
| | | ADAM-5056SO | 16-ch Source Type Isolated DO w/LED |
| | | ADAM-5055S | 16-ch Isolated DI/O w/LED |
| | | ADAM-5060 | 6-ch Relay Output |
| | | ADAM-5069 | 8-ch Power Relay Output w/LED |
| | | ADAM-5081 | 4-ch/8-ch High Speed Counter/Frequency |

Fully Integrated Advantech Remote I/O Solutions

Modbus/TCP Master/slave/RTU Protocol Support

Integration of ADAM-2000/4000/6000 and APAC 5000 remote IO

